

Franklin Home Power

The Franklin Home Power (FHP) system integrates multiple on-site sources of power generation into a robust energy control system that is managed via a simple mobile app. FHP contains an aGate, the FranklinWH mobile app and aPower batteries.



aGate - Intelligent Energy Controller

- Micro-grid interconnect device (MID)
- Stackable continuous output power 5kW to 38.4kW
- Compatible with any brand of solar inverter and standby generator
- Optional Smart Circuits Module for intelligent load management (installed internally)
- Optional Generator Module, for intelligent integrations of standby generators in power infrastructure
- Outage detection with < 16ms seamless power transfer
- Compatible for grid-tied and off-grid applications
- MPU avoidance with NEC 2017, NEC 2020 and UL1741 PCS Certification

aPower - Lithium Iron Phosphate Battery

- LFP cell battery, scalable 13.6–204kWh (15 units per aGate)
- 12-year warranty, 43MWh energy throughput

FranklinWH App - Easy Energy Management

- Simple one-touch programming for Self-Consumption, Time of Use, and Emergency Backup operations
- Redundant communication options ensure connectivity: Ethernet, Wifi, 4G
- Quick and easy commissioning with remote diagnostic capabilities
- Real-time and historic energy monitoring and control of power generation and consumption, in one app

Performance

| | |
|---------------------------------------|--|
| Battery Chemistry | Lithium Iron Phosphate (LFP) |
| Usable Battery Energy | 13.6 kWh per unit, scalability up to 15 units ¹ |
| Aggregate Throughput | 43 MWh |
| Communications | Ethernet / 4G / Wifi |
| Nominal AC Voltage | 120V / 240V, 60 Hz |
| Continuous / Peak Discharge Power | 5 kW / 10 kW |
| Switch Over Time (grid to micro-grid) | <16 ms |
| Round Trip Efficiency | 89% ² |
| Noise Emission (optimal) | <30 dB (A) |
| User Interface | FranklinWH App |
| Warranty | 12 years |

Electrical Interface

| | |
|--------------------|------------------|
| Coupling | AC Coupled |
| Feed-in Phase | Split Phase |
| Connection Support | L1 / L2 / N / PE |

Work Modes

| |
|------------------|
| Self-Consumption |
| Time of Use |
| Emergency Backup |

| | |
|-------------------------------------|-------|
| Maximum Supply Fault Current | 20 kA |
|-------------------------------------|-------|

Electrical Connections

| | |
|--|--|
| aPower Over Current Protection Device | 100A Max |
| Solar Input Over Current Protection Device | 80A Max |
| Backup Load Port Over Current Protection Device | 200A Max |
| Generator Over Current Protection Device ³ | 200A Max |
| Smart Circuits Over Current Protection Device ⁴ | Opt. a 1 × 80A Max @240 V & 1 × 50A Max @240V Opt. b 1 × 80A Max @240 V & 2 × 50A Max @120V |

Mechanical

| | |
|------------------------|---|
| Dimensions (H × W × D) | aGate: 31.5 × 21.7 × 6.3 in (800 × 550 × 160 mm) aPower: 45.3 × 29.5 × 11.4 in (1150 × 750 × 290 mm) |
| Weight | aGate: 50 lb (23 kg) aPower: 408 lb (185 kg) |
| Installation | Wall mount or floor mount |

Environmental

| | |
|-------------------------|--|
| Operating Temperature | -4°F to 122°F (-20°C to 50°C) |
| Operating Humidity (RH) | Up to 100% RH, condensing |
| Altitude | Maximum 9,843 ft (3,000 m) |
| Ingress Rating | IP67 (Battery and power converter system) IP56 (Wiring compartment) |
| Storage Condition | 14°F to 113°F (-10°C to 45°C) Up to 95% RH, non-condensing |
| Enclosure Type | NEMA type 3R |
| Environment | Indoor and outdoor rated |

Compliance & Certificates

| | |
|---------------|---|
| Certificates | aGate: UL 1741 PCS, UL 67 ⁵ , UL 869A ⁵ , UL 916 ⁵ , CAN/CSA C22.2 No. 107.1-16 aPower: UL 9540, UL 1741SA, UL 1741SB, UL 1973, UL 9540A, IEEE 1547, IEEE 1547.1, UN 38.3, CAN/CSA C22.2 No. 107.1-16 |
| Seismic | AC156, OSHPD, IEEE 693-2005 (high) |
| Environmental | California Proposition 65 RoHS Directive 2011 / EU |
| Emissions | FCC Part 15 Class B, ICES 003 |

1: Please contact us for solution design support if you have large capacity requirements.

2: At beginning of life, AC to battery to AC, 50% power rating.

3: Generator Module is optional.

4: Smart Circuit Module is optional.

5: Sections from these standards were used during the safety evaluation and included in the UL 1741 listing.

Address: 1731 Technology Dr., Suite 530 San Jose, CA 95110 **Telephone:** +1 888-837-2655 **Email:** info@franklinwh.com **Website:** www.franklinwh.com

Copyright 2023 FranklinWH Energy Storage Inc. All rights reserved. The Franklin logo, FranklinWH, and other trademarks or service names are the trademarks of FranklinWH Energy Storage Inc. The document is for informational purposes only, data subject to change. 2023-05-23

